



FICHA TÉCNICA

Technical Data Sheet

Mármol en acabado mate / Matte finish marble | 80 X 160 CM. / 32 X 64 IN. | Porcelanato esmaltado. Rectificado. / Glazed porcelain tile. Rectified.

6 Caras / 6 Faces |
 PEI 4 Alto Tráfico / High Traffic |
 Variación Alta / High Variation |
 100% Pasta Blanca / White body

Uso / Usage

Interior / Interior |
 Baño / Bathroom |
 Cocina / Kitchen |
 Exterior / Exterior |
 Comercial / Commercial

Porcelanato mate / Matte porcelain tile

Características técnicas / Technical specifications

	Pasta blanca / White body								
	Separación de boquilla / Grout size	2 mm							
	PEI	4							
	Resistencia química / Chemical resistance	Conforme	ASTM C650						
	DCOF / Dynamic Coefficient of Friction	>0.42	ASTM C1028						
	Absorción de agua / Water absorption	≤0.5%	ASTM C373						
	MOHS	5-8	ASTM C1028						
	Resistencia de flexión / Breaking strength	>350 kg	ISO 10545-4						
	Shock térmico / Thermal shock resistance	Conforme	ASTM C484						
	Resistencia a helada / Frost resistance	Conforme	ASTM C1026						
	Resistencia a manchas / Stain resistance	Conforme	ASTM C1378						
	Resistencia de abrasión / Abrasion resistance	Conforme	ANSI A137						
	Información de Embalaje / Packaging Information	<table border="1"> <thead> <tr> <th>PZS-CAJA / PCS-BOX</th> <th>M²-CAJA / FT²-BOX</th> <th>KG-CAJA / LBS-BOX</th> </tr> </thead> <tbody> <tr> <td>2</td> <td>2.56 / 27.55</td> <td>59.65 / 131.5</td> </tr> </tbody> </table>	PZS-CAJA / PCS-BOX	M ² -CAJA / FT ² -BOX	KG-CAJA / LBS-BOX	2	2.56 / 27.55	59.65 / 131.5	
PZS-CAJA / PCS-BOX	M ² -CAJA / FT ² -BOX	KG-CAJA / LBS-BOX							
2	2.56 / 27.55	59.65 / 131.5							

Cesantoni S.A. de C.V. certifica que los resultados anteriores fueron obtenidos en análisis de laboratorio elaborado por el departamento de Control de Calidad.

Cesantoni certifies that the above results were obtained in laboratory testing performed by the quality control department.

www.cesantoni.com.mx | contacto@cesantoni.com.mx

